

TECHNICAL DATASHEET (244/2009/EC)

Modeltype: LED E14 C37 6W 600lm

Technical data:

| | |
|----------------------------------------------------------------------------------------|--------------------------------|
| Brandname: | TEDi |
| Energy efficiency category: | A+ |
| Weighted energy consumption (kWh/h): | 0.006kWh/h |
| Nominal luminous flux (lm): | 600lm |
| Nominal life time (h): | 25000h |
| Number of switching cycles: | 15000 |
| Colour temperature (k): | 3000k |
| Warm-up time up to 60% of the full light output (s): | <2s |
| Light flux control (dimnable): | No |
| Is the lampe optimized to use for non-standard conditions? | No |
| Lamp dimensions (length and diameter (mm)): | 37*97mm (+/-3mm) |
| Equivalence with an incandescent lamp (W): | 48W |
| If the lamp is called 'energy saving lamp' does it complies the efficacy requirements? | Yes |
| If contains, lamp mercury content (mg): | 0 |
| Website to consult in case of accidental lamp breakage: | TEDi.com (guideline for lamps) |
| Rated wattage (W): | 6.0W +/- 10% |
| Rated luminous flux (lm): | 600lm +/- 10% |
| Rated lamp life time (h): | 25000h |
| Lamp power factor: | >0.5 |
| Lumen maintenance factor at the end of the nominal life (%): | ≥ 70% |
| Starting time (Time up to optimal operation (s)): | < 0.5s |
| Colour rendering (Ra): | > 80 |
| Instructions on how to clean up the lamp debris in case of accidental lamp breakage: | see guideline (TEDi.com) |
| Recommendations on how to dispose of the lamp at its end of life: | see guideline (TEDi.com) |

